


# CX Software and Hardware - Datasheet

## CX Software

This suite of programs is designed to work with the kamailio PBX software as a cross-platform GUI client and the supporting server side applications necessary for the features of the GUI application to work with kamailio. The client-side GUI apps are available as web pages running AJAX scripted web pages(Chrome recommended)

| Component        | Description                   |
|------------------|-------------------------------|
| Voice Engine     | Kamailio / Freeswitch         |
| Dataabase        | MariaDB                       |
| Web Server       | Nginx                         |
| Script Language  | PHP 5 and Perl                |
| Modules          | CPAN modules                  |
| Client Software  | Browser Firefox or Chrome     |
| Client Softphone | SIP based (Eyebeam or Zoiper) |
| Voice Protocols  | SIP                           |
| Voice Codes      | G729 / G.711 ulaw, alaw       |



## CX Hardware

CX hardware is made of 1U server-type appliance with certain components that make machine work for VoIP software. Modified machine strictly follow REGULATORY TYPE E10S002 and safty standards of EMC EMISSIONS CLASS – A.

| Component            | Description  |
|----------------------|--|
| Formm Factor         | 1U   |
| CPU                  | Intel® Xeon® Processors                                  |
| Storage              | SSD in RAID (M2 storage if Archive Storage is installed) |
| RAM                  | 8GB  |
| Archive Storage      | SATA   |
| M.2 Storage          | High IOPS to speed up loading times                      |
| Telephony Intterface | Only External Gateways to save CPU from Overloading      |
| Ethernet             | 1 / 2  |
| USB                  | 2 / 3 Stanndard  |